




Nominal Rivet Diameter	(L) Nominal Rivet Body Length	(F) Nominal Blind Side Protrusion	Grip Range	Rivet Part Number	Hole Size					Shear Strength	Tensile Strength
						(D) Body Diameter	(H) Flange Thickness	(E) Flange Diameter	(W) Nominal Mandrel Diameter		
In. (mm)	In. (mm)	In. (mm)	In. (mm)		In. (mm)	In. (mm)	In. (mm)	In. (mm)	In. (mm)	Lbs. (N)	Lbs. (N)
5056 Aluminum Body/Steel Mandrel – Domed Head – Finish: Plain/Protective Coating											
1/8 (3.2)	.250 (6.4)	.415 (10.5)	.031-.094 (.8-2.4)	EAD 42 BS	.129-.133 (3.28-3.38)	.122-.128 (3.10-3.25)	.032-.040 (0.81-1.02)	.238-.262 (6.05-6.66)	.076 (1.93)	210 (935)	325 (1446)
	.313 (8.0)	.478 (12.1)	.095-.156 (2.4-4.0)	EAD 43 BS							
	.375 (9.5)	.540 (13.7)	.157-.218 (4.0-5.5)	EAD 44 BS							
5/32 (4.0)	.400 (10.2)	.565 (14.4)	.188-.218 (4.8-5.5)	EAD 54 BS	.160-.164 (4.06-4.17)	.153-.159 (3.89-4.04)	.039-.047 (0.99-1.19)	.296-.328 (7.52-8.33)	.095 (2.41)	340 (1513)	490 (2181)
5056 Aluminum Body/Steel Mandrel – Large Flange – Finish: Plain/Protective Coating											
1/8 (3.2)	.375 (9.5)	.540 (13.7)	.157-.218 (4.0-5.5)	EAD 44 BS LF	.129-.133 (3.28-3.38)	.122-.128 (3.12-3.28)	.057-.065 (1.45-1.65)	.360-.390 (9.14-9.91)	.076 (1.93)	210 (935)	325 (1446)
C1006-C1010 Steel Body/Steel Mandrel – Domed Head – Finish: Zinc/Protective Coating											
1/8 (3.2)	.250 (6.4)	.415 (10.5)	.031-.094 (.8-2.4)	ESD 42 BS	.129-.133 (3.28-3.38)	.122-.128 (3.10-3.25)	.032-.040 (0.81-1.02)	.238-.262 (6.05-6.66)	.076 (1.93)	295 (1313)	425 (1891)
	.313 (8.0)	.478 (12.1)	.095-.156 (2.4-4.0)	ESD 43 BS							
	.375 (9.5)	.540 (13.7)	.157-.218 (4.0-5.5)	ESD 44 BS							
3/16 (4.8)	.425 (10.8)	.660 (16.8)	.126-.218 (3.2-5.5)	ESD 64 BS	.192-.196 (4.88-4.98)	.183-.191 (4.65-4.85)	.047-.055 (1.19-1.40)	.359-.391 (9.12-9.93)	.114 (2.90)	590 (2626)	815 (3627)
	.550 (14.0)	.785 (19.9)	.251-.343 (6.4-8.7)	ESD 66 BS							
C1006-C1010 Steel Body/Steel Mandrel – Large Flange – Finish: Zinc/Protective Coating											
1/8 (3.2)	.375 (9.5)	.540 (13.7)	.157-.218 (4.0-5.6)	ESD 44 BS LF	.129-.133 (3.28-3.38)	.122-.128 (3.10-3.25)	.032-.040 (0.81-1.02)	.360-.390 (9.14-9.91)	.076 (1.93)	295 (1313)	425 (1891)