





Nominal Rivet Diameter	(L) Nominal Rivet Body Length	(F) Nominal Blind Side Protrusion	 Grip Range	Rivet Part Number	 Hole Size					 Shear Strength	 Tensile Strength
						(D) Body Diameter	(H) Flange Thickness	(E) Flange Diameter	(W) Nominal Mandrel Diameter		
In. (mm)	In. (mm)	In. (mm)	In. (mm)		In. (mm)	In. (mm)	In. (mm)	In. (mm)	In. (mm)	Lbs. (N)	Lbs. (N)
C1006-C1010 Steel Body/Steel Mandrel – Domed Head – Finish: Zinc/Zinc											
1/8 <i>(3.2)</i>	.250 <i>(6.4)</i>	.452 <i>(11.5)</i>	.063-.125 <i>(1.6-3.1)</i>	SD 42 SP.093	.129-.133 <i>(3.28-3.38)</i>	.122-.128 <i>(3.10-3.25)</i>	.031-.041 <i>(0.79-1.04)</i>	.238-.262 <i>(6.05-6.66)</i>	.076 <i>(1.93)</i>	450 <i>(2001)</i>	350 <i>(1556)</i>
	.329 <i>(8.4)</i>	.528 <i>(13.4)</i>	.150-.195 <i>(3.8-4.9)</i>	SD 43 SP.165							
	.391 <i>(19.93)</i>	.590 <i>(15.0)</i>	.185-.240 <i>(4.6-6.0)</i>	SD 44 SP.185							
	.507 <i>(12.9)</i>	.706 <i>(17.9)</i>	.312-.360 <i>(7.9-9.1)</i>	SD 46 SP.312							
5/32 <i>(4.0)</i>	.437 <i>(11.1)</i>	.669 <i>(17.0)</i>	.205-.260 <i>(5.2-6.6)</i>	SD 55 SP.218	.160-.164 <i>(4.06-4.17)</i>	.152-.158 <i>(3.86-4.01)</i>	.040-.050 <i>(1.02-1.27)</i>	.296-.328 <i>(7.52-8.33)</i>	.095 <i>(2.41)</i>	525 <i>(2335)</i>	500 <i>(2224)</i>
	.562 <i>(14.3)</i>	.794 <i>(20.2)</i>	.241-.368 <i>(6.1-9.3)</i>	SD 56 SP.241							
3/16	.315 <i>(8.0)</i>	.612 <i>(13.8)</i>	.062-.125 <i>(1.5-3.1)</i>	SD 62 SP.093	.192-.196 <i>(4.88-4.98)</i>	.183-.191 <i>(4.65-4.85)</i>	.045-.058 <i>(1.14-1.47)</i>	.355-.393 <i>(9.02-9.98)</i>	.114 <i>(2.90)</i>	900 <i>(4005)</i>	700 <i>(3113)</i>
	.378 <i>(9.6)</i>	.668 <i>(17.0)</i>	.065-.187 <i>(1.6-4.7)</i>	SD 63 SP.130							
	.440 <i>(11.2)</i>	.702 <i>(17.8)</i>	.181-.272 <i>(4.6-6.9)</i>	SD 64 SP.220							
	.700 <i>(17.7)</i>	.950 <i>(24.1)</i>	.376-.500 <i>(9.6-12.7)</i>	SD 68 SP.437							
1/4 <i>(6.4)</i>	.365 <i>(9.3)</i>	.650 <i>(16.5)</i>	.062-.125 <i>(1.5-3.1)</i>	SD 82 SP.093	.257-.261 <i>(6.53-6.63)</i>	.249-.255 <i>(6.32-6.48)</i>	.066-.076 <i>(1.69-1.95)</i>	.475-.525 <i>(12.06-13.34)</i>	.151 <i>(3.84)</i>	1750 <i>(7788)</i>	1400 <i>(6227)</i>
C1006-C1010 Steel Body/Steel Mandrel – Large Flange – Finish: Zinc/Zinc											
5/32 <i>(4.0)</i>	.300 <i>(7.6)</i>	.503 <i>(12.8)</i>	.063-.125 <i>(1.6-3.1)</i>	SD 52 SP LF.093	.160-.164 <i>(4.06-4.17)</i>	.152-.158 <i>(3.86-4.01)</i>	.057-.073 <i>(1.45-1.85)</i>	.448-.488 <i>(11.38-12.40)</i>	.095 <i>(2.41)</i>	525 <i>(2335)</i>	500 <i>(2224)</i>
	.417 <i>(10.6)</i>	.628 <i>(16.0)</i>	.129-.256 <i>(3.3-6.5)</i>	SD 54 SP LF.129							
	.525 <i>(13.3)</i>	.794 <i>(20.17)</i>	.126-.343 <i>(3.2-8.7)</i>	SD 56 SP LF.129							
3/16 <i>(4.8)</i>	.442 <i>(11.2)</i>	.579 <i>(14.7)</i>	.187-.235 <i>(4.7-6.0)</i>	SD 64 SPR LF.187*	.192-.196 <i>(4.88-4.98)</i>	.184-.190 <i>(4.67-4.83)</i>	.071-.091 <i>(1.80-2.31)</i>	.600-.650 <i>(15.24-16.51)</i>	.114 <i>(2.90)</i>	900 <i>(4005)</i>	700 <i>(3113)</i>
	.575 <i>(14.6)</i>	.79 <i>(20.1)</i>	.210-.327 <i>(5.3-8.3)</i>	SD 65 SPR LF.225*							
	.566 <i>(14.4)</i>	.716 <i>(18.1)</i>	.188-.38 <i>(4.7-9.7)</i>	SD 66 SPR LF.210*							
	.566 <i>(14.4)</i>	.716 <i>(18.1)</i>	.210-.375 <i>(5.3-9.3)</i>	SD 66 SPR LF.225*							
	.700 <i>(17.9)</i>	.918 <i>(23.3)</i>	.407-.467 <i>(10.3-11.8)</i>	SD 68 SP LF.225							

(*) R: Recessed Body